

Adaptive Urban Dispersion Modeling (AUDIM)



Andy Wissink, Kyle Chand

Center for Applied Scientific Computing

Branko Kosovic


Atmospheric Sciences - NARAC






Prediction of aerosol dispersion is a critical homeland security need

- Biomeland Security Organization
 Lawrence Uterancy Billional Laboratory
- High fidelity models that predict the spread of airborne hazardous materials are important
 - Assist in emergency planning and response scenarios
 - Guide effective sensor placement
 - Event reconstruction (with measurements)








Objective



 Develop an <u>operational</u> CFD capability to predict aerosol dispersion of hazardous materials in an urban environment.








FEM3MP CFD Model




- FEM3MP is the primary urban dispersion modeling code used in the atmospheric sciences division in NARAC
- Validated from experiments
 - Joint urban 2003 in Oklahoma City
 - Urban 2000 in Salt Lake City
 - Windtunnel experiments







Release south of downtown (A)




Release in downtown area (B)



Utilize Complex Geometry Embedded Boundary Cartesian Methods for Buildings





- Constructing body-fitted logically rectangular grids is tedious and expensive.
- Embedded boundary grids constructed automatically in SAMRAI
 - Built from polygons or from surface triangulation using CUBES
 - Refinement enhances accuracy of boundary representation



Example embedded boundary mesh constructed with CUBES

M. Berger, Courant Inst./NASA Ames






DHS 7-04 DHS-5




Utilize advanced meshing tools developed at LLNL



- Overture project has tools for rapid geometry-to-mesh (Rapsodi)
 - Rapid construction of surface grids from CAD data
 - Developed to handle complex geometries



- SAMRAI library supports parallel AMR applications
 - Adaptive mesh refinement (AMR) automatically enhances simulation resolution where needed.
 - Runs on large parallel computer systems





Couple advanced technologies to develop enhanced operational tool



FEM3MP

CFD code for urban dispersion

SAMRAL

Parallel adaptive mesh support

Overture

Rapid geometry to mesh capability


Next-generation Integrated Urban Dispersion Capability


- Automatic mesh construction from building datasets.
- Geometrically complex buildings and cityscapes
- Diverse urban environments: stadiums, arenas, subways, etc.
- Adaptive mesh refinement for enhanced fidelity: release points, building entrances, etc.
- Complex release scenarios: moving sources, etc.



Rapsodi/Eleven : geometry tools for efficient support of EB grid generation

- Rapsodi : Overture subset that provides Computer Aided Design (CAD) support
 - IGES reader for complex CAD geometries
 - Extensive CAD fixup and editing utilities






- Eleven: a small, independent library for EB grid generation
 - Geometry representation, query and modification
 - Query API that takes advantage of blockstructured AMR data structures
 - Can be called from inside a solver (e.g. SAMRAI) to evaluate geometry when generating refinement patches



Rapsodi: CAD geometry editing tools








Metro/Eleven: Interactive tools for modifying geometry





Modify/Add/Delete buildings Clip out regions of interest XML geometry database Perl-scriptable text interface Metro is built upon the ELEVEN geometry library







Automatic construction of grids from building datasets



 Tool developed to read polygonal geometry data from NARAC and generate Cartesian adaptive grids.



Polygonal geometry data (Salt Lake City)



Adaptive volume mesh by metro/CUBES




Grid generation time reduced from weeks to minutes




Downtown Salt Lake City gridding example

 Structured grid constructed with existing tools required about 1 week



 Adaptive cut-cell grid generated with metro/CUBES required about 2 minutes


> 1.7M gridpoints, 6 levels refinement Surface grid – 30 sec with "metro" Volume grid – 45 sec with "CUBES"





Tools utilized to mesh complex cityscapes






Midtown Manhattan

Times Square






Polygonal geometry representation by metro (3600+ polygons)




Agile geometry tools for EB applications








Integrated approach will enable automated geometry to CFD analysis





SAMRAI/Eleven links enable modeling of complex cityscapes






Eleven
Inside/outside
determination

SAMRAI
Mesh
construction

- Generating triangulated surface difficult or impossible
- Inside/outside determination using Polygons




through refinement



Project tasks and timeline



- Demonstration calc with prototypes
- Demonstrate geometry-to-mesh capability
- Develop complex geometry in SAMRAI
- Deliver gridding tools for NYC
- SAMRAI-FEM3MP integration
- Develop cut cell FE algs
- Develop AMR capability
- Deliver adaptive flow solver
- Fine-tune performance for operational use






First set of delivered tools are being used for Manhattan studies

NSP | Bonolad Socarity Organization

Manhattan simulations

- DHS-funded Urban Dispersion Project (UDP)
- Meshing tools used for CFD simulations



Manhattan meshes Rapsodi/SAMRAI




CFD Calculation (non-adaptive)
FEM3MP

DHS 7-04 DHS-18




Grid adaptivity will significantly reduce flow solution time





Uniform grid (non-adaptive)

33.6 M gridcells



AMR grid **3.4 M** gridcells

Lower Manhattan – Madison Sq. Garden/Empire State building

Resolution: 5m horizontal, 2m vertical



Algorithmic research issues being addressed in this work




DHS-20

 Finite element boundary representation on cut-cell grids using "fictitious domain" algorithm



- Adaptive algorithms for finite element CFD solver
- Turbulence models



velocity (m/s)
1.50
1.25
1.00
0.75
0.50
0.25

RANS

 Building geometry information that incorporates new features (e.g. terrain)




Future: Coupling image processing technologies to simulation




Automated airborne LIDAR-to-grid capability

- Currently use building shapefile input limited number of cities available
- LIDAR data available for almost any US city



Higher resolution building geometry

- Better resolution of building facades
- Extensions to large indoor spaces



A. Zakhor, UC Berkeley




AUDIM will be a part of NARAC operational capability



World-wide data coverage

- . Real-time weather data
- . Terrain & land surface
- . Maps



Plot valid 06 Oct 2000 21:00:00 to 06 Oct 2000 22:00:00 UTC



National Center at LLNL

- Advanced, automated 3-D modeling system
- Scientific and technical staff provides quality assurance and assistance 24 hrs x 7 days


Real-time Hazard Advisories

- . Nuclear, radiological, chemical, biological & natural releases
- . National center predictions available within minutes using Internet/Web tools
- . Deployed modeling tools on end user's computer
- . Geographical information displays
- . Affected population, health risks, recommended actions



Need: Efficient, flexible, and accurate operational urban dispersion capability





- Current CFD urban dispersion models are research and planning rather than operational tools
- Operational urban plume dispersion tool must be fast, flexible and accurate



Priorities for improving dispersion modeling addressed in recent NRC report



NRC of the National Academies report "Tracking and Predicting the Atmospheric Dispersion of Hazardous Material Releases – Implications for Homeland Security"

"New dispersion modeling constructs need to be further explored and possibly adapted for operational use in urban setting. This includes advanced short execution models, slower but more **accurate computational fluid dynamics** and **large-eddy simulation** models and models with adaptive grids." (page 5.)

- "... no one system had all the features that the committee deemed critical:
- accommodation of urban and complex topography
- accurate though slower models for the preparedness and recovery phase"



Event Reconstruction Answers the Critical Questions: What? When? Where? How Much?





- Atmospheric releases are one of the most highly effective and rapid means to impact large populations
- Primary uncertainty due to unknown sources and meteorology
- Our approach couples data and predictive models to provide
 - Backwards analyses to determine unknown source characteristics
 - Optimal forward predictions for consequence assessment
 - Dynamic reduction in uncertainty as additional data become available




Urban Dispersion Modeling using FEM3MP



Our current capability:

- FEM3MP a stand-alone CFD code
 - finite element code (terrain/shape following coordinates)
 - parallelized using MPI
 - solves steady state and time dependent problems



Current Limitations:

- Limited capability for simulation of fast evolving flows
- Treatment of inflow, outflow and lateral boundary conditions
- Range of release scenarios
- Simpler geometries
- Labor-intensive grid generation capability

DHS 7-04 DHS-26




We use experimental measurements to verify and validate urban dispersion code

400



Miran A, 1.37 m above sfc

Joint-Urban 2003 in Oklahoma City (took place in July 2003)





DHS 7-04 **DHS-27**




Seamless coupling between regional and urban scale models will be possible







URBAN SCALE
1m grid size




Coupling will provide accurate boundary conditions for urban scale simulations



Accurate time dependent forcing is essential for prediction of dispersion






More accurate urban dispersion prediction will be achieved through seamless coupling with a mesoscale model which will provide time dependent forcing for urban-scale flows




Predicted Wind Vectors and Concentrations in Downtown OKC



(a) Through Release Point



(b) Through Sonic Building







Oklahoma City Downtown Modeled with Explicitly Resolved and Virtual Buildings



Height in Log10(meters)









We use virtual building technique for efficient representation of buildings



Comparison between surface dispersion patterns 2m above surface for a hypothetical release



Fully-resolved results



Virtual representation


10m uniform grid resolution




Conclusions



- We are developing new capabilities by combining expertise and tools from two groups at LLNL – COMP and NARAC
- Automatic geometry-to-mesh and adaptive gridding tools will significantly enhance NARAC's operational urban capability
- Tools developed are already being used (for studies in Manhattan) and have the potential to become the standard urban simulation capability in NARAC.







Acknowledgments



- This work was performed under the auspices of the U.S. Department of Energy by University of California Lawrence Livermore National Laboratory under contract No. W-7405-Eng-48.
- Document UCRL-PRES-208459

DHS 7-04 DHS-34